

## BATTERY CHARGER, SOLDIER PORTABLE CHARGER (SPC)



**TAMCN: A0012**

**ID: 11099A**

**NSN: 6130-01-495-2839**

### Functional Description

The Battery Charger, Soldier Portable Charger (SPC), (PP-8498/U) is a dual-channel sequential charger that automatically charges up to eight batteries (two at a time) in approximately eight hours. The SPC comes with (4) J-6358B/P (BB-2590/U – BB-390B/U) adapters. All other adapters are ordered separately. The SPC operates from AC or DC power.

### Technical Description

#### Battery Charger

Manufacturer: Bren-Tronics  
Model: PP-8498/U

#### Dimensions

Length (in): 22.8  
Width (in): 14.6  
Height (in): 9  
Weight (lbs): 27.5  
Volume (ft<sup>3</sup>): 1.8

#### Power

Input: 90 -260 VAC  
22- 28 VDC  
Frequency (Hz): 47-420

#### Warranty

4 years from MFG date

#### Adapter

#### Adapter NSN

#### Battery

#### Battery

J-6358B/P	5940-01-501-3312	BB-2590/U	BB-390B/U
J-6357A/P	5940-01-493-6388	BB-388A/U	BB-2588/U
J-6356/P	5940-01-427-9183	BB-326/U	BB-516A/U
J-6355/P	5940-01-427-9247	BB-503A/U	
J-6354/P	5940-01-427-9278	BB-2847A/U	
J-6523A/P	5940-01-492-7238	BB-557/U	BB-2557/U
J-6521/P	5940-01-467-8813	BB-2600A/U	
J-6587/P	5940-01-493-6750	BB-2800/U	
J-6589/P	5940-01-493-7622	NIMH / NICAD	
J-6588/P	5940-01-493-6751	MBITR (PRC-148)	
J-6769A/P	5940-01-526-8017	BB-2001A/U (CSEL)	
J-6878/P	5940-01-573-9693	FALCON (PRC-152)	
J-6879/P	5940-01-573-9697	IISR (PRC-153)	

Climatic Conditions: Operating: +14°F to +104°F is recommended. Accepted for short duration: -4°F to +122°F. Storage Temperature Range: -40°F to +158°F.

#### NAVAL CERT MESSAGE

The SPC has been certified for use and storage aboard Naval Surface Vessels. For further info contact PM EPS, Project Officer for this item.

**NOTES:** Requires periodic software upgrades as new adapters become available. For vehicle DC operation the DC cable must be ordered separately, J6362A/U, NSN 5940-01-501-6714.